Vastewater

9SN Series



Applications


 Little Giant 9SN Series Sewage Pumps are rated for continuous duty in effluent and sewage wastewater transfer applications


Features


- 4/10 hp PSC motor with thermal overload protection
 - Energy saving low amp draw
 - Cooler running motor which extends the life of the pump
- Cast iron pump housing with protective epoxy coating for corrosion and rust resistance
- Stainless steel screws, bolts and handle
- Mechanical seals (stainless steel spring, nitrile parts, carbon and ceramic faces)
- Upper sintered sleeve bearing and lower ball bearing
- Handles liquid and solid waste materials up to 2" diameter
- Avaliable in manual or automatic operation:
- Piggyback mechanical float switch
 - On level 9"- 14"
 - Off level 2"- 6"
- Integral Snap Action float switch
 - On level 9"- 12"
 - Off level 3"- 6"
- Two year warranty

Little GIANT.

Engineering Data








9SN-CIA-SFS

9SN-CIA-RF



9SN-CIM

Specifications

								Performa	ance GPM	l @ Head					Dimensions		
Item	Model	Listing (S)	НР	Volts	Solids Size (dia. In.)	Discharge	Running Amps/ Watts	5'	10'	15'	Shut Off (ft)	PSI	Cord Length	Weight (lbs)	HXLXW (in)		
509228	9SN-CIA-SFS	cCSAus	4/10	115	2"	2"	8.5/850	110	70	30	20	8.7	20'	35.5	13.12	10.54	6.8
509204	9SN-CIA-RF	cCSAus	4/10	115	2"	2"	8.5/850	110	70	30	20	8.7	20'	35.5	11.4	11.64	6.8
509215	9SN-CIA-RF	cCSAus	4/10	115	2"	3"	8.5/850	110	70	30	20	8.7	20'	35.5	11.4	11.64	6.8
509226	9SN-CIM	cCSAus	4/10	115	2"	3"	8.5/850	110	70	30	20	8.7	20'	35.5	11.4	11.64	6.8
509203	9SN-CIM	cCSAus	4/10	115	2"	2"	8.5/850	110	70	30	20	8.7	20'	34.5	11.4	11.64	6.8

Construction						
Cover	Epoxy-coated cast iron/ *Thermoplastic					
Motor Housing	Epoxy-coated cast iron					
Impeller Material	Nylon					
Impeller Type	Vortex					
Volute	Epoxy-coated cast iron					
Power Cord	SJTW					
Mechanical Shaft Seal	Nitrile with carbon and ceramic faces					
Fasteners	Stainless Steel					
Shaft	Steel					
Bearings	Upper sintered sleeve and lower ball bearing					

^{*}SFS Models

Franklin Electric P.O. Box 12010

Oklahoma City, OK 73157-2010 Phone: 1.800.701.7894 Fax: 1.800.678.7867 www.LittleGiantPump.com

Performance Data

