

**thermoplastic automatic submersible SUMP PUMPS**

These sump pumps provide carefree performance and quiet operation. Each is corrosion-resistant with a screened top inlet. Discharge features a unique 1-1/4" inside thread with a 1-1/2" outside thread for maximum versatility on replacement jobs.

FPOS3250A  
FPOS2450A



FPOS3200A  
FPOS2400A



FPOS1800A



**FEATURES**

- Automatic submersible sump pump
- Maximum pumping – see performance chart on following page
- Corrosion-resistant composite construction
- 115V overload protected motor
- Automatic or manual operation
- 8' grounded power cord
- 1-1/4" or 1-1/2" discharge pipe size

**FPOS3250A**

**1/2 HP**

**BEST 3 year warranty**

- Maximum pumping capacity to 3630 gallons per hour
- Can be used in narrow 10" diameter sump basin
- Most popular submersible series

**FPOS3200A**

**1/2 HP**

**BEST 3 year warranty**

- Maximum pumping capacity to 3630 gallons per hour
- Can be used in 14" diameter sump basin
- Most popular submersible series

**FPOS2450A**

**1/3 HP**

**Better 2 year warranty**

- Maximum pumping capacity to 3150 gallons per hour
- Can be used in narrow 10" diameter sump basin

**FPOS2400A**

**1/3 HP**

**Better 2 year warranty**

- Maximum pumping capacity to 3150 gallons per hour
- Can be used in 14" diameter sump basin

**FPOS1800A**

**1/4 HP**

**Good 1 year warranty**

- Maximum pumping capacity to 2880 gallons per hour
- Can be used in 14" diameter sump basin

**thermoplastic automatic submersible SUMP PUMPS (cont.)**

**PERFORMANCE INFORMATION** (Based on using 1-1/4" discharge pipe)

Rating	Warranty (years)	Model	HP	Switch Type	Min. Sump Diameter	Float Switch		Performance - Gallons per Hour at Discharge Head in Feet					Maximum Lift (no flow)
						On	Off	0'	5'	10'	15'	20'	
BEST	3	FPOS3250A	1/2	Vertical	10"	8"	3.5"	3630	3200	2700	2000	1200	24 ft.
BEST	3	FPOS3200A	1/2	Float	14"	14"	6"	3630	3200	2700	2000	1200	24 ft.
Better	2	FPOS2450A	1/3	Vertical	10"	8"	3.5"	3150	2760	2160	1410	-	20 ft.
Better	2	FPOS2400A	1/3	Float	14"	14"	6"	3150	2760	2160	1410	-	20 ft.
Good	1	FPOS1800A	1/4	Float	14"	12.5"	4.5"	2880	2280	1620	660	-	18 ft.

**ACCESSORIES** (sold separately, see page 10)


**Required:**

Check Valve	FP0026-6D or FP0026-10
Flood Alarm	FPW217-242
Discharge Hose Kit	FP0012-6F 1-12" x 24' or FP150-24 1-2" x 24'

**Optional:** (see page 8)

Battery Back-Up	FP1800DCC or FP2800DCC
-----------------	------------------------

**TYPICAL APPLICATION**



**DID YOU KNOW?**

If you currently have a pedestal pump, it can quickly and easily be replaced with a submersible. A submersible sump pump has many advantages over a pedestal pump, such as: quieter operation, more product selection from horsepower to gallons of water per hour moved, and it's safer because the pump is fully submersed rather than extending outside the sump pit.

**DID YOU KNOW?**

If you have a sump pump you should consider the purchase of a Flotec Emergency Back-Up Sump Pump System. These systems are a back-up in case of power loss or primary sump pump failure to protect your home and valuables. Flotec offers 2 systems: FP1800DCC and FP2800DCC along with the supporting batteries and acid solutions. Please ask your retailer or call customer service at 1-800-365-6832 for assistance.

**DID YOU KNOW?**

When replacing a sump pump, you should always replace your check valve.