

StormPro® BA75

Heavy Duty 3/4 HP Sump Pump

DATA SHEET

Updated: 12/03/2012

Document Name: StormPro_BA75_DS Page 1 of 1



Discharge: 2" N.P.T. Female, Vertical
Liquid Temperature: 104°F
Motor Housing: Stainless Steel (304)
Pump Strainer: Stainless Steel (304)
Impeller: Non-Clogging Vortex, Cast Iron
Shaft: Stainless Steel (410)
O-Rings: Buna-N
Hardware: Stainless Steel
Seal: Dual Mechanical, Type 21, Oil Lubricated
Material:
 Rotating Faces: Silicon Carbide
 Stationary Faces: Silicon Carbide
Upper Bearing: Single Row, Ball, Oil Lubricated
Lower Bearing: Single Row, Ball, Oil Lubricated
Motor: Single Phase, Permanent Split Capacitor (PSC) Includes Thermal Overload Protection, Class B Insulation
Minimum Pit Diameter: 10"

Model	Output		Discharge (inch)	Rated		Maximum		Dimensions L x W* x H	Weight (lbs)
	HP	Amp		Head (feet)	Flow (GPM)	Head	Flow		
BA75	3/4	7.5	2	10	84	0 GPM @ 35'	98 GPM @ 0'	8¾" x 5¼" x 14½"	25

Available Models: BA75I (6" Ion™ Digital Level Control switch), BA75SPI (SPI switch), BA75M (manual). *Add ¾" to width for Ion™ Digital Level Control switch

