

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



PUMP COMPANY

Zoeller Family of Water Solutions™

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
www.zoeller.com

COMPARE THESE FEATURES

- Non-clogging vortex impeller design bronze class 88-8-0-4 (180 Series)
- Enclosed impeller design (191 Series)
- Float-operated, submersible (NEMA 6) 2-pole mechanical switch
- Durable cast construction. Cast iron switch case, base, motor and pump housing. No sheet metal parts to rust or corrode.
- Stainless steel screws, bolts, float rod, handle, guard, arm and seal assembly
- 20 ft. UL Listed 3-wire neoprene cord and plug. Extra cord lengths available in 25-35-50 foot length only.
- Motor - 60 Hz, 3450 RPM, oil-filled, hermetically sealed, automatic reset, thermal overload protected (1 Ph only)
- Maximum temperature for effluent or dewatering 130°F (54°C), WD189 120°F (49°C)
- Variable level control systems available
- Square ring & gasket - neoprene
- Shaft seal - carbon & ceramic rotary face seal with stainless steel wetted parts
- Upper & lower ball bearings running in bath of oil
- All 180/4180 series pass 3/4" spherical solids
Model 191 pump passes 5/8" spherical solids
- On point 15-3/4" • Off point 5 1/4" (automatic units)
- Major width 12-3/4" • Height 19-5/16" (single seal pumps)
- 1-1/2" NPT discharge with 2" or 3" flange available (model 191 is not available with 3" flange)
- Corrosion-resistant powder coated epoxy finish

MODELS 4185-4186-4188-4189 DOUBLE SEAL PUMPS (Nonauto only)

- Protects motor from seal leaks
- Improved bearing lubrication.
- Helps eliminate seal and bearing damage from dry runs.
- Major width 12-3/4" • Height 21-3/16"

Note: The sizing of effluent systems normally requires variable level float(s) controls and properly sized basins to achieve required pumping cycles or dosing timers with nonautomatic pumps.

AUTOMATIC UNITS NOT RECOMMENDED FOR USE IN EFFLUENT SYSTEMS

*NOTE: No UL Listing for 200/208 1 Phase Pumps, Model 186 & 191, or Double Seal Series.

Nonautomatic Model for variable level systems

See Back Page for UL & CSA Listings

185 - 186 - 188 - 189 Single-Seal Series 4185 - 4186 - 4188 - 4189 Double-Seal Series 191 Single-Seal Drip Pump (For Pump Prefix Identification see News & Views 0052)



Tested to UL Standard UL778
& Certified to CSA
Standard C22.2 No. 108



HIGH HEAD FLOW-MATE

FOR SEPTIC TANK • LOW PRESSURE PIPE (LPP)
AND ENHANCED FLOW STEP SYSTEMS

EFFLUENT

OR DEWATERING PUMP • SUBMERSIBLE

1-1/2" NPT DISCHARGE STANDARD • 2" or 3" FLANGE AVAILABLE



230V Automatic
Controlled by variable
level float switch
integral to the pump in
WD189/WD4189
Series only.



Double
Seal
Pump



230V/1 Ph Automatic
Available in 185,
186, 188,
189 Series



230V/1 Ph
Nonautomatic
Available in
185/4185,
186/4186,
188/4188,
189/4189 Series



SELECTION GUIDE

1. Integral float operated mechanical switch, no external control required.
2. For automatic use single piggyback variable level float switch or double piggyback variable level float switch. Refer to FM0477.
3. See FM1228 for correct model of simplex control panel.
4. See FM0712 for correct model of duplex control panel.
5. Variable level control switch 10-0743 used as a control activator, specify simplex (3) float or duplex (4) float system. Refer to FM0526.

⚠ CAUTION

All installation of controls, protection devices and wiring should be done by a qualified licensed electrician. All electrical and safety codes should be followed including the most recent National Electrical Code (NEC) and the Occupational Safety and Health Act (OSHA).

185 MODELS	4185 MODELS	Standard all models - 20 ft. cord - 1 HP			Control Selection		Listings	
Single Seal	Double Seal	Volts - Ph	Mode	Amps	Simplex	Duplex	cCSAus	UL
D185	---	230 1	Auto	9.8	1	---	Y	Y
E185	E4185	230 1	Non	9.8	2 or 3	4	Y	Y
*H185	---	200 1	Auto	11.5	1	---	Y	N
*I185	*I4185	200 1	Non	11.5	2 or 3	4	Y	N
*F185	*F4185	230 3	Non	7.4	3 & 5	4 & 5	Y	Y
*J185	*J4185	200 3	Non	7.5	3 & 5	4 & 5	Y	Y
*G185	*G4185	460 3	Non	3.7	3 & 5	4 & 5	Y	Y
*BA185	---	575 3	Non	3.3	3 & 5	4 & 5	Y	N
186 MODELS	4186 MODELS	Standard all models - 20 ft. cord - 1-1/2 HP			Control Selection		Listings	
Single Seal	Double Seal	Volts - Ph	Mode	Amps	Simplex	Duplex	cCSAus	UL
D186	---	230 1	Auto	13.7	1	---	Y	N
E186	E4186	230 1	Non	13.7	2 or 3	4	Y	N
*H186	---	200 1	Auto	17.2	1	---	Y	N
*I186	*I4186	200 1	Non	17.2	2 or 3	4	Y	N
*F186	*F4186	230 3	Non	9.2	3 & 5	4 & 5	Y	N
*J186	*J4186	200 3	Non	10.3	3 & 5	4 & 5	Y	N
*G186	*G4186	460 3	Non	4.6	3 & 5	4 & 5	Y	N
*BA186	*BA4186	575 3	Non	3.6	3 & 5	4 & 5	Y	N
188 MODELS	4188 MODELS	Standard all models - 20 ft. cord - 1-1/2 HP			Control Selection		Listings	
Single Seal	Double Seal	Volts - Ph	Mode	Amps	Simplex	Duplex	cCSAus	UL
D188	---	230 1	Auto	14.0	1	---	Y ⁽²⁾	Y ⁽¹⁾
E188	E4188	230 1	Non	14.0	2 or 3	4	Y	Y ⁽¹⁾
*H188	---	200 1	Auto	16.8	1	---	Y	N
*I188	*I4188	200 1	Non	16.8	2 or 3	4	Y	N
*F188	*F4188	230 3	Non	8.9	3 & 5	4 & 5	Y	Y
*J188	*J4188	200 3	Non	10.3	3 & 5	4 & 5	Y	Y
*G188	*G4188	460 3	Non	4.6	3 & 5	4 & 5	Y	Y
*BA188	---	575 3	Non	3.5	3 & 5	4 & 5	Y	N
189 MODELS	4189 MODELS	Standard all models - 20 ft. cord - 2 HP			Control Selection		Listings	
Single Seal	Double Seal	Volts - Ph	Mode	Amps	Simplex	Duplex	cCSAus	UL
D189	---	230 1	Auto	17.1	1	---	Y ⁽²⁾	Y ⁽¹⁾
E189	E4189	230 1	Non	17.1	2 or 3	4	Y ⁽²⁾	Y ⁽¹⁾
*H189	---	200 1	Auto	20.5	1	---	Y	N
*I189	*I4189	200 1	Non	20.5	2 or 3	4	Y	N
*F189	*F4189	230 3	Non	11.2	3 & 5	4 & 5	Y	Y
*J189	*J4189	200 3	Non	13.2	3 & 5	4 & 5	Y	Y
*G189	*G4189	460 3	Non	6.0	3 & 5	4 & 5	Y	Y
*BA189	*BA4189	575 3	Non	5.8	3 & 5	4 & 5	Y	N
*WD189	*WD4189	230 1	Auto	17.1	1	4	N	N
191 MODELS		Standard all models - 20 ft. cord - 2 HP			Control Selection		Listings	
Single Seal	Double Seal	Volts - Ph	Mode	Amps	Simplex	Duplex	cCSAus	UL
E191	---	230 1	Non	14.5	2 or 3	4	Y	N


* no molded plug

(1) UL Listed unit available with 20 Amp plug.

(2) CSA Approval with 20 Amp plug.

(3) 20 Amp Outlet, P/N 10-0060 must be used.

For information on additional Zoeller products refer to catalog on Piggyback Variable Level Float Switches, FM0477; Electrical Alternator, FM0486; Mechanical Alternator, FM0495; Sump/Sewage Basins, FM0487; Simplex Pump Control, FM1596; Alarm Systems, FM0732; and Disconnect/Rail Systems, FM0787.




009903


WARNING: Model 185 should not be subjected to heads less than 30 feet TDH.

Single Seal-180 Series
Automatic Design
Weight 82-89 lbs.

Double Seal-4180 Series /
Weight 89-94 lbs.



SK374



SK1413

RESERVE POWERED DESIGN

For unusual conditions a reserve safety factor is engineered into the design of every Zoeller pump.



PUMP COMPANY

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

Your Peace of Mind is Our Top Priority®

visit our web site:
www.zoeller.com

