

# CRAFTSMAN<sup>®</sup>

**1/3-1/2** HP MOTOR<sup>™</sup>

## SUMP PUMPS

**AUTOMATIC SUBMERSIBLE**



TYPICAL BASEMENT SUMP APPLICATION SHOWN

### PUMPS INCLUDE

1/3 HP CMXWUSD62348  
1/2 HP CMXWUSD62558

Submersible Sump Pump  
Automatic Float Switch  
Owners Manual

1/3 HP CMXWUSD62313

1-1/2 in. Check Valve  
Submersible Sump Pump  
Automatic Float Switch  
Owners Manual



**CMXWUSDUMP**

**3 YEAR**<sup>™</sup>  
**LIMITED**  
**WARRANTY**

WE BUILD PRIDE<sup>™</sup>

# SUMP PUMPS

### VERTICAL FLOAT SWITCH

CUSTOMIZED SJE RHOMBUS V2 TESTED OVER 2M CYCLES

### PIGGY-BACK POWER PLUG

ABILITY TO BYPASS SWITCH TO MANUALLY OPERATE PUMP

### THERMAL OVERLOAD PROTECTION

PROTECTS PUMP FROM OVERHEATING

### SOLID COPPER MOTOR WINDING

IMPROVES PERFORMANCE AND PUMP LONGEVITY

### 1-1/2 IN. FPT DISCHARGE

HIGH FLOW PERFORMANCE

### QUAD-FOOT BASE

PROVIDES ADDITIONAL STABILITY WHEN IN USE

### BUILT-IN HANDLE

FOR EASY INSTALLATION

### THERMOPLASTIC PUMP MATERIAL

### SPLIT CAPACITOR

STRONG START-UP WITH ENERGY EFFICIENT OPERATION

### 1/3 HP OR 1/2 HP PUMP MOTOR

POWERFUL / RELIABLE

### OIL COOLED MOTOR

IMPROVES PERFORMANCE

### INTEGRAL SCREEN

FILTERS OUT DEBRIS AND EASILY REMOVABLE



### CMXWUSDCV69502 - CHECK VALVE



Included in kit \*CMXWUSD62313 or can be purchased separately



### SPECIFICATIONS

Model	CMXWUSD62348	CMXWUSD62313*	CMXWUSD62558
Horsepower	1/3 HP		1/2HP
Check Valve	No	Yes	No
Switch Type	Vertical		
Discharge Size	1-1/2 in. FPT		
Cord Length	10 ft.		
Voltage	120		
Pump Construction	Thermoplastic		
Impeller Material	Thermoplastic		
Warranty	3 Years		

### PERFORMANCE

Model	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.	25 ft.
CMXWUSD62348	3500	3200	2600	1950	900	-
CMXWUSD62313*	3500	3200	2600	1950	900	-
CMXWUSD62558	4100	3700	3200	2500	1500	100



CRAFTSMAN® is a registered trademark of Stanley Black & Decker, Inc., used under license.  
© 2022 CRAFTSMAN

Pedrollo Group Inc.  
45 Maryland Ave East  
St. Paul, MN 55117  
Phone: 888-331-4569

Form: 601501 Rev. 6/2022