

30ACi+

Battery Backup System

- Fully automatic auxiliary power source
- Backup system runs on AC or DC power
- Runs the same 1/3 HP pump with power on or off

44 GPM

@ 10' TDH

• Ion+[®] digital level control sensor with integrated alarms



37 Forestwood Dr., Romeoville, IL 60446 www.ionproducts.net [815] 886-9200 Patents Pending, Patent No. 8,591,198, 9,033,686 and 9,680,401

3 YEAR

WARRANTY



Typical Installation Diagram




- 1. Battery box with inverter
- 2. 1/3 HP WC33 sump pump
- 3. Ion+ digital level control/alarm sensor
- 4. Recommended minimum basin size: 18" x 24" (not included)

30ACi+ with **lon+** - Part Number: **MET20372** 30ACi+ with **lon+ Connect Cellular** - Part Number: **MET20487** 30ACi+ with **lon+ Connect WiFi** - Part Number: **MET20493**

System Performance



Pump Performance



System Specifications

- 1/3 HP pump with PSC, energy efficient motor: 4.0 amps
- Up to 45 GPM
- Fully automatic, converts 12 volt DC to 120 volt AC when utility power is lost
- Runs 1/3 HP pump on AC or DC power
- Inverter has digital display, tells status of system at all times
- Requires one 12 volt deep cycle AGM battery (battery is NOT included)

- Non-corrosive battery enclosure
- Includes piggyback lon+ digital level control/alarm sensor with no moving parts
 - Built-in alarm and monitoring system with Power, System and High Water LEDs and audible alarm
 - Dry contacts to connect to a monitoring device via an RJ11 connection
- Quick and easy installation
- 3 year warranty