

Safety Data Sheet

Issue Date: 06-AUGUST-2020

Section 1 – Chemical Products and Company Identification

Product name/Product identifier:

Maintenance Free Sealed Lead Acid Battery

Model

B12-75, BW-27 AGM, B12-90, B12-100

UNID No.:

Complies with UN2800 Classification

Details of the supplier safety data sheet:

Glentronics, Inc. 645 Heathrow Drive Lincolnshire IL 60069

Emergency Telephone number:

Company phone number 800-991-0466

Emergency Telephone (24 Hr) CHEMTREC 1-703-527-3887 (International)

1-800-424-9300 (North America)

Section 2 - HAZARDS IDENTIFICATION

Classification

Health Hazard: May cause cancer. May cause damage to fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Corrosion: Causes skin burns and severe irritation or damage to eyes.

Harmful: Harmful if swallowed. Harmful if inhaled.

Hazards Not Otherwise Classified (HNOC)

Harmful if swallowed.

This battery has passed the vibration test, pressure differential test and leakage test at 55 degrees C according to recommendations on the transport of dangerous goods model registration (15th) special provision 238. It is not restricted to IATA DGR according to special provision A67 and is not restricted to IMGD code according to special provision 238.

Signal Word

Danger

Hazard Statements

Health Hazard: May cause cancer. May cause damage to fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Corrosion: Causes skin burns and severe irritation or damage to eyes.

Harmful: Harmful if swallowed. Harmful if inhaled.







Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Do not handle until all safety precautions have been read and understood

Do not eat, drink or smoke when using this product

Wear respiratory protection

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Report No.: STT20150127046R Page 1 of 9

Precautionary Statements - Response

Immediately call a poison center or doctor/physician

Eye Exposure: Rinse cautiously with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call poison control or doctor/physician

Skin/Hair Exposure: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician

Swallowed: Rinse mouth. Do not induce vomiting. Immediately call a poison center or doctor/physician

Precautionary Statements - Storage

Store in a cool well ventilated area. Keep away from ignition sources, heat and flame. Batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to avoid: Strong oxidant, combustible materials and corrosives.

Precautionary Statements - Disposal

Dispose of item with an approved waste disposal facility

Section 3 – INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Concentration
Inorganic Lead/Lead Compounds	7439-92-1	~ 48%
Lead Dioxide	1309-60-0	~ 22%
Sulfuric Acid	7664-93-9	~ 15%
Container Plastics (ABS or PP)	9003-56-9 (ABS) 9003-07-0 (PP)	~ 10%
Fiberglass Separator	65997-17-3	~ 4%
Tin	7440-31-5	~ 0.85%
Calcium	7440-70-2	~ 0.15%

Section 4 - FIRST-AID MEASURES

First Aid Measures

General Advice

Provide SDS to medical personnel for treatment

Eye Contact

Rinse cautiously with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call poison control or doctor/physician

Skin Contact

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician

Ingestion

Rinse mouth. Do not induce vomiting. Immediately call a poison center or doctor/physician

Most important symptoms and effects

Symptoms

Causes skin burns and severe irritation to eyes

Report No.: STT20150127046R Page 2 of 9

Indication of any immediate medical attention and special treatment needed

Note to Physician

Continued washing of the affected area with cold water will be helpful in removing the last traces of sulfuric acid. Creams or ointments should not be applied before or during the washing phase of treatment

Section 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, sandy soil, carbon dioxide or appropriate foam.

Unsuitable Extinguishing Media

Not determined

Specific Hazards Arising from the Chemical

Emit toxic fumes under fire conditions

Protective equipment and precautions for firefighters

Wear self contained breathing apparatus pressure demand, MSHA/OSHA (approved or equivalent) and full protective gear to prevent contact with skin or eyes.

Section 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions

Wear protective clothing as described in section 8. Ventilate affected area

Environmental Precautions

Prevent from entering into the soil, ditches, sewers, waterways and or groundwater. See section 12 for additional information.

Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material. Neutralize runoff with lime, soda ash, etc.

Methods for Clean-Up

Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

Prevention of Secondary Hazards

Material can create slippery conditions.

Section 7 – HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Wash face, hands, and any exposed skin thoroughly after handling. Follow all SDS/label precautions even after container is emptied, because it may retain product residues. Do not breathe vapors or spray mist. Do not eat, drink or smoke when handling this product. Use only with adequate ventilation. Wear respiratory protection. Loosen closure carefully; relieve internal pressure when received and at least weekly thereafter. Do not use pressure to empty. Do not wash out container or use it for other purposes. Replace closure after each use.

Keep away from ignition sources, heat and flame. Batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to avoid: Strong oxidant, combustible materials and corrosives.

Conditions for safe storage, including any incompatibilities

Report No.: STT20150127046R Page 3 of 9

Storage Conditions

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from incompatible materials. Store locked up.

Keep away from ignition sources, heat and flame. Batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to avoid: Strong oxidant, combustible materials and corrosives.

Incompatible Materials

Vigorous reactions with water; alkaline solutions; metals, metal powder; carbides; chlorates; nitrates; strong oxidizing, reducing, or combustible organic materials. Hazardous gases are evolved on contact with chemicals such as cyanides, sulfides, and carbides.

Section 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sulfuric Acid	TWA: 0.2 mg/m3 thoracic	TWA: 1 mg/m3	IDLH: 15 mg/m3
7664-93-9	fraction	(vacated) TWA: 1 mg/m3	TWA: 1 mg/m3

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Use chemical safety goggles and/or a full face shield.

Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory

If the exposure limit is exceeded and engineering controls are not feasible, a full-face respirator with an acid gas cartridge and particulate filter (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerin, etc.) are present, use a NIOSH type R or P particulate filter. For emergencies or instances where the exposure levels are not known, use a full-face shield positive-pressure, air-supplied respirator. WARNING: Air purifying respirators do not protect workers in oxygen-deficient atmospheres. Where respirators are required, you must have a written program covering the basic requirements in the OSHA respirator standard. These include training, fit testing, medical approval, cleaning, maintenance, cartridge change schedules, etc. See 29CFR1910.134 for details.

General Hygiene Considerations

Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

Section 9 – PHYSICAL/CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid

AppearanceClear liquidOdorOdorless

Color Clear Odor Threshold Not determined

Property Values Remarks • Method

pH < 1.0

Report No.: STT20150127046R Page 4 of 9

Melting Point/Freezing Point 10% - (25°F)

51% - (-30°F)

Boiling Point/Boiling Range 10% - (210°F)

51% - (270°F)

Flash Point Will not burn, non-flammable

Evaporation Rate < 1.0

Flammability (Solid, Gas)

Upper Flammability Limits

Lower Flammability Limit

Not determined

Not determined

Vapor Pressure < 0.3 mmHg @ 25°C (77°F)

 Vapor Density
 3.4
 (Air=1)

 Specific Gravity
 1.058-1.409
 @ 60°F

Water Solubility

Solubility in other solvents

Partition Coefficient

Auto-ignition Temperature

Decomposition Temperature

Kinematic Viscosity

Dynamic Viscosity

Not determined

20°C 25mPas
0°C 60mPas

Explosive Properties Not an explosive
Oxidizing Properties Not determined

Section 10 - STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Will react with water or steam to produce toxic and corrosive fumes. Reacts with carbonates to generate carbon dioxide gas, and with cyanides and sulfides to form poisonous hydrogen cyanide and hydrogen sulfide respectively

Chemical Stability

Stable under ordinary conditions of use and storage. Concentrated solutions react violently with water, spattering and liberating heat.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources. Heat, moisture, incompatibles. Keep separated from incompatible substances.

Hazardous Decomposition Products

Releases sulfur dioxide at extremely high temperatures. Toxic fumes of oxides of sulfur when heated to decomposition.

Section 11 - TOXICOLOGY INFORMATION

Information on likely routes of exposure

Product Information:

Eye Contact Causes severe eye damage. **Skin Contact** Causes severe skin burns.

Inhalation May cause irritation to the mucus membranes and upper respiratory tract.

Ingestion May be harmful if swallowed.

Component information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sulfuric Acid 7664-93-9	Sulfuric Acid = 2140 mg/kg (Rat)		= 510 mg/m³ (Rat) 2 h

Information on physical, chemical and toxicology effects

Symptoms

Please see section 4 of this SDS for symptoms

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

IARC has classified "strong inorganic acid mist containing sulfuric acid" as a Category 1 carcinogen, substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid. Inorganic mist is not generated under normal use of this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sulfuric Acid	A2	Group 1	Known	X
7664-93-9				

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of

Labor)

X - Present

Numerical measures of toxicity

Not determined

Section 12 – ECOLOGICAL INFORMATION

An environment hazard cannot be excluded in the event of unprofessional handling or disposal.

Lead and its compounds can result in a threat if released into the environment.

In most surface water and groundwater, lead forms compounds out of the water column. Lead my occur absorbed ions or surface coatings on sediment mineral particles or may be carried in colloidal particles in surface water. Most lead is strongly retained in soil, resulting in little mobility, Lead may be immobilized by ion exchange with hydrous oxides or by chelation with humic or fulvic acids in the soil. Leak (dissolved phase) is bioaccumulated by plants and animals, both aquatic and terrestrial.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sulfuric Acid		500: 96 h Brachydaniore rerio		29: 24 h Daphnia magna
7667-93-9		mg/L LC50 static		mg/L EC50

Persistence/Degradability

When released into the soil, this material may leach into groundwater. When released into the air, this material may be

removed from the atmosphere to a moderate extent by wet deposition. When released into the air, this material may be removed from the atmosphere to a moderate extent by dry deposition.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

Section 13 – DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes:

Lead-acid batteries are completely recyclable. Return whole scrap batteries to distributor, manufacturer or lead smelter for recycling. Disposal should be in accordance with applicable regional, national and local laws and regulations. Contact local and/or state environmental officials regarding disposal information.

Contaminated Packaging:

For neutralized spills, place residue in acid-resistant containers with sorbent material, sand or earth and dispose of in accordance with local, state and federal regulations for acid and lead compounds. Contact local and/or state environmental officials regarding disposal information.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Sulfuric Acid	Toxic
7664-93-9	Corrosive

Section 14 – TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN2800

Proper Shipping NameBatteries, wet, non-spillable, and electrical storage

Hazard Class 8
Packing Group III
Reportable Quantity (RQ) 1000 lbs

IATA

UN/ID No UN2800

Proper Shipping NameBatteries, wet, non-spillable, and electrical storage

Hazard Class 8
Packing Group III

IMDG

UN/ID No UN2800

Proper Shipping Name Batteries, wet, non-spillable, and electrical storage

Hazard Class 8
Packing Group III

Section 15 – REGULATORY INFORMATION

International Inventories

TSCA Listed DSL Listed **NDSL** Listed **EINECS** Listed **ELINCS** Listed **ENCS** Listed KECL Listed **PICCS** Listed **AICS** Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sulfuric Acid	1000 lb.	1000 lb.	RQ 1000 lb final RQ
7664-93-9			RQ 454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardNoSudden Release of Pressure HazardNoReactive HazardYes

SARA 313

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Sulfuric Acid - 7664-93-9	7664-93-9	1-51	1.0

CWA (Clean Water Act)

Component	CWA -Reportable Quantities	CWA - Toxic Pollutants	CWA Priority Pollutants	CWA - Hazardous Substances
Sulfuric Acid	1000 lb.			X
7664-93-9				

US State Regulations

California Proposition 65


This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Sulfuric Acid - 7664-93-9	Carcinogen

U.S. State Right-to-Know Regulations

Report No.: STT20150127046R Page 8 of 9

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Sulfuric Acid	X	X	X
7664-93-9			



Section 16 – OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	3	0	2	W
<u>HMIS</u>	Health Hazards	Flammability	Instability	Special Hazards
	3	0	2	Not Determined

Issue Date: 02-Feb-2015
Note: New format

The Safety Data Sheet (SDS) was generated by the submitted information in accordance with regulation (EC) No.1907/2006, Regulation (EC) No 1272/2008, EU Commission Directive 67/548/EEC, 1999/45/EC, for details please refer to attached pages.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet