

CAST IRON SURFACE EFFLUENT PUMP

APPLICATIONS

Ideal for pumping liquid from septic tanks, as well as pumping out flooded basements, irrigation, and general dewatering.

FEATURES & BENEFITS

- Easy to prime to 25'; no additional priming required after initial fill
- Built-in check valve
- Rugged cast iron casing
- Heavy-duty motor, 115/230 Volts
- Cast iron impeller



Model	Item No.	UPC	HP	Volts	Discharge	Gallons Per Hour at Height				Shut-Off	Max. Pressure (PSI)
						20'	30'	40'	50'		
RL-S50	621810	0 10121 12643 5	1/2	115/230	1-1/4" FNPT	2700	1860	960	-	49'	21
RL-S75	621826	0 10121 12647 3	3/4	115/230	1-1/4" FNPT	3480	2640	1740	600	56'	24

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-S50	10.25"	20"	11.75"	42	1.39	32	8	4
RL-S75	10.25"	20"	11.75"	44	1.39	32	8	4

Cast Iron Surface Effluent Pumps

