

THERMOPLASTIC SUMP PUMPS

APPLICATIONS

Ideal for light- to high-volume water removal in residential spaces such as basements and crawl spaces.

FEATURES & BENEFITS

- Automatic submersible sump pumps
- 1-1/2" FNPT discharge with 1-1/4" FNPT adapter included
- Piggyback float switch
- PSC motor and closed vane impeller design
- Double seal system
- 8' cord



RL-SP50T

RL-SP50V

Model	Item No.	UPC	HP	Volts	Switch	Amps	Cord Length	Gallons Per Hour at Height					Shut-Off	On/Off Levels	Min. Basin Diameter
								0'	5'	10'	15'	20'			
RL-SP25T	14942739	0 10121 14162 9	1/4	115	Tethered	6.0	8'	2900	2640	2100	1560	540	23'	On: 14.5" Off: 5.5"	14" or more
RL-SP33T	14942740	0 10121 14163 6	1/3	115	Tethered	4.4	8'	3200	2880	2520	1680	1260	25'	On: 14.5" Off: 5.5"	14" or more
RL-SP33V	14942741	0 10121 14164 3	1/3	115	Vertical	4.4	8'	3200	2880	2520	1680	1260	25'	On: 7.25" Off: 2.75"	11" or more
RL-SP50T	14942742	0 10121 14165 0	1/2	115	Tethered	4.4	8'	3600	3060	2520	1920	1320	28'	On: 14.5" Off: 5.5"	14" or more
RL-SP50V	14942743	0 10121 14166 7	1/2	115	Vertical	4.4	8'	3600	3060	2520	1920	1320	28'	On: 7.25" Off: 2.75"	11" or more

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-SP25T	7.5"	9.25"	11.75"	9.5	0.47	104	26	4
RL-SP33T	7.5"	9.25"	11.75"	11.5	0.47	104	26	4
RL-SP33V	9.05"	9.25"	13.5"	11	0.65	60	20	3
RL-SP50T	7.75"	9.25"	11.75"	14	0.49	104	26	4
RL-SP50V	9.05"	9.25"	13.5"	13	0.65	60	20	3

